

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

# UV-IPC2318LE-ADF40KM-WP

Uniview




## Features

---

- Uniview
- IP Bullet Camera - Easy Range
- 8 MP (3072X1728)
- 4 mm Lens
- Minimum illumination 0.0003 lux | 0 Lux with supplemental lighting
- White light range 30m
- ColorHunter with Wise-ISP technology: with Uniview's Wise-ISP technology, your images will reach an exceptional level of perfection. This intelligent processor optimizes each frame by reducing noise, improving dynamic range and adjusting colors to deliver superior visual quality. Designed for scenarios with varying light conditions, Wise-ISP guarantees sharp and consistent images, becoming the basis for Uniview's most advanced solutions
- SIP (Smart Intrusion Prevention) Lite: combines artificial intelligence algorithms with real-time video analysis to accurately identify human intrusions, minimizing false alarms caused by animal movements or weather conditions
- UMD (Ultra Motion Detection): thanks to its advanced AI algorithm, UMD is able to detect changes in the environment extremely efficiently, even in conditions of high speed or motion difficult to capture by other technologies
- WDR 120dB
- Integrated microphone
- Slot for microSD up to 512 GB
- Corridor mode 9:16
- PoE
- IP67
- Graphene and metal
- ONVIF Compatible

## Specifications

<b>Brand</b>	Uniview
<b>Range</b>	Easy
<b>Image sensor</b>	1/1.8" Progressive Scan CMOS
<b>Maximum resolution</b>	8 Megapixel (3840x2160)
<b>Main Stream rate</b>	8MP (3840*2160)@20fps; 5MP (3072*1728)@30fps; 4MP (2560*1440)@30fps; 1080P (1920*1080)@30fps; 720P (1280*720)@30fps
<b>Extra Stream rate</b>	1080P (1920*1080)@30fps; 720P (1280*720)@30fps; D1 (720*576)@30fps; 640*360@30fps; 2CIF (704*288)@30fps; CIF (352*288)@30fps
<b>Compression</b>	Ultra265/H.265/H.264
<b>Lens</b>	2.8 mm (H: 111°, V: 63°, D: 131°)
<b>Minimum illumination</b>	Color Hunter with WISE-ISP technology, which allows to display a full color image 24/7 with total clarity 0.0003Lux (F1.0 AGC ON)
<b>White LED range</b>	30 m
<b>Corridor Mode</b>	Yes (9:16)
<b>Image improvements</b>	WDR (120dB), HLC, BLC, 2D/3D-NR, ROI, Privacy Mask, Smart IR
<b>Audio</b>	Built-in microphone   G.711
<b>Internal memory</b>	MicroSD card, Max 512 GB
<b>Video Backup</b>	ANR video recovery technology by installing a Micro SD card
<b>Events</b>	Motion Detection, UMD, Audio Detection, Tamper protection
<b>UMD</b>	Yes (Advanced motion detection with human and vehicle classification)
<b>Intelligent functions</b>	Smart Intrusion Prevention (Lite) Intrusion, line crossing (both detections based on human and vehicle detection)
<b>Network interface</b>	Ethernet 10/100M BaseT
<b>Remote access</b>	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
<b>Interoperability</b>	ONVIF
<b>Reset button</b>	Yes
<b>Power</b>	DC 12 V / 3.9 W, PoE IEEE802.3af



<b>Temp. operation</b>	-30° C ~ 60° C
<b>Degree of protection</b>	Waterproof IP67, Surge protection 4KV
<b>Material</b>	Metallic
<b>Dimensions</b>	73 (W) x 73 (H) x 206 (D) mm
<b>Weight</b>	480 g