

RACKS

NETWORK CABINET



Product Web Page



NS-502GL24U6060

A NETWORK CABINET IS A COMBINATION OF HARDWARE STRUCTURES DESIGNED TO ACCOMMODATE TECHNICAL EQUIPMENT INCLUDING (ROUTERS, SWITCHES, HUBS, UPS, CABLES) AND, OF COURSE, SERVERS.

NETWORK CABINET RACK 24U 60*60

FEATURES

- Best sales and famous model floor rack.
- Reliable structure, static loading capacity: 800KGs (Optional castors and plinth).
- Adjustable feet and heavy duty castors are available simultaneously, moving conveniently and fixing reliably.
- Baying together easily, quickly, efficiently and firmly.
- Glass front door with metal panel and rear metal door or high density vented front door and rear doors, meeting the requirements of mechanical protection and ventilation.
- Optional cable entry on top cover and bottom panel.
- Front, rear door and side panel can be removed facility, the bottom has the function of ventilation and rat-proof.
- Varies optional accessories, reliable quality.
- Optional opening hole and varies specification upon customers' special requirements
- 7 heights: 22U,24U,27U,32U,37U,42U,47U (Can customize).
- Many depth option: 600/800/900/960/1000/1100/1200mm.
- Flexible packing methods allows for convenient stocking and end user delivery.
- Multiple sizes available.
- Customization requests welcome

STANDARD AND MATERIAL

Comply with

ANSI/EIA;RS-310-D;IEC297-2; DIN41491:PART1;
DIN41494:PART7; GB/T3047.2-92
Standard and ETSI standard.(grey).

SURFACE TREATMENT

degreasing,pickling, phosphoric, powder coating

MATERIAL

SPCC cold rolled steel.

THICKNESS

Mounting profile 2.0mm;
the others:1.0-1.2mm.

COLOR

Body color:RAL9004(black); RAL7035(grey).

TECHNICAL SPECIFICATION

Model	U	Width	Depth	Height
NS-502GL22U6060	22	600	600	1080
NS-502GL24U6060	24			1150
NS-502GL27U6060	27			1300
NS-502GL32U6060	32			1525
NS-502GL37U6060	37			1745
NS-502GL42U6060	42			1965
NS-502GL47U6060	47			2190

Remark : height above the height of the cabinet without wheels

