

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-106S3

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 6 CH
- 64 Mbps bandwidth supported
- Maximum resolution 6 Megapixel
- Supports intelligent functions
- Ultra compression 265/H.265/H.264
- Audio output
- Full HD HDMI and VGA Output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 6 TB
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible

Specifications

| | |
|---|--|
| Brand | Uniarch |
| Inputs for IP cameras | 6 IP Channels |
| IP compatible cameras | UNIVIEW, ONVIF |
| Main Stream recording | 6Mpx / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF |
| Decoding | 1x6Mpx@ 30fps / 1x5MPx @ 30fps / 2x4MPx @ 30fps / 2x3MPx @ 30fps / 4x1080p @ 30fps / 8x720p @ 30fps / 16xD1 @ 25fps |
| Bidirectional audio | 1 RCA output |
| Video outputs | 1 HDMI Full HD, 1 VGA |
| Video compression format | Ultra H.265 / H.265 / H.264 |
| Display resolution | 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768 |
| Total bandwidth | 64 Mbps downstream / 48 Mbps upstream |
| General functions | Motion detection, human body detection, video loss, alarm input * To receive alarm input events, a camera with alarm inputs is required |
| Intelligent functions from the camera | Area intrusion, line crossing, area entry, area exit, audio detection and Auto-Tracking configuration on PTZs * You need an IP camera with these functions to be able to make configurations and searches from the recorder |
| SIP (Smart Intrusion Prevention) from the camera | Supported in 4CH. Alarm reception only, no alarm image reception) * IP camera with SIP function required |
| External Backup | USB / HDD USB memory |
| Internal memory | 1 SATA HDD 3.5" of up to 6 TB (not included) |
| Communication | 2 x USB 2.0 / 1 x RJ45 (Ethernet) |
| Remote access | Web browser, Smartphone App & PC Software |
| Power supply | DC 12 V, <6W (No hard disk) |
| Operating temperature | -10°C ~ +55°C |
| Dimensions / Weight | 42(AI) x 190 (An) x 195(Fo) mm / 1 Kg |