

IP CCTV / Professional NVRs / Uniview - Uniarch

# UV-NVR-116S3

Uniarch



## Features

---

- Uniarch
- NVR for IP cameras
- 16 CH
- 64 Mbps bandwidth supported
- Maximum resolution 6 MP
- SIP
- UMD
- Compression Ultra265/H.265/H.264
- Audio output
- Full HD HDMI and VGA Output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 6 TB
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible

## Specifications

---

<b>Brand</b>	Uniarch
<b>Inputs for IP cameras</b>	16 CH
<b>IP compatible cameras</b>	UNIVIEW, ONVIF
<b>Main Stream recording</b>	6Mpx / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
<b>Decoding</b>	2x6MP@30, 4x5MP@25, 4x4MP@25, 4x3MP@25, 6x1080P@30, 8x720P@30, 16xD1
<b>Bidirectional audio</b>	1 RCA output
<b>Video outputs</b>	1 HDMI Full HD, 1 VGA
<b>Video compression format</b>	Ultra H.265 / H.265 / H.264
<b>Display resolution</b>	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
<b>Total bandwidth</b>	64 Mbps downstream / 48 Mbps upstream
<b>General functions</b>	Motion detection, human body detection, video loss, alarm input * To receive alarm input events, a camera with alarm inputs is required
<b>Intelligent functions from the camera</b>	Area intrusion, line crossing, area entrance, area exit. * You need an IP camera with these functions to be able to make configurations and searches from the recorder
<b>SIP (Smart Intrusion Prevention) from the camera</b>	Supported in 4CH. Alarm reception only, no alarm image reception) * IP camera with SIP function required
<b>External Backup</b>	USB / HDD USB memory
<b>Internal memory</b>	1 SATA HDD 3.5" of up to 6 TB (not included)
<b>Communication</b>	2 x USB 2.0 / 1 x RJ45 (Ethernet)
<b>Remote access</b>	Web browser, Smartphone App & PC Software
<b>Power supply</b>	DC 12 V, <7W (No hard disk)
<b>Operating temperature</b>	-10°C ~ +55°C
<b>Dimensions / Weight</b>	42(AI) x 190 (An) x 195(Fo) mm / 1 Kg