

Analogue CCTV / HD 4n1 / Cameras / Bullet Cameras

UV-UAC-B112-F28-W

Uniview



Features

- Uniview
- Analog Bullet Camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (2880x1620)
- 2.8 mm Lens
- 0.02 Lux
- White light range 20 m
- Weatherproof IP67
- TVI/AHD/CVI/CVBS
- COLORHUNTER

Specifications

Range	Uniview
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2MP
Main Stream rate	1080p (1920x1080)
Extra Stream rate	720p (1280x720)
Lens	2.8 mm
Viewing Angle (FOV)	90.5° (H), 49.6° (V), 109.5° (D)
Minimum illumination	0.02 Lux (Colour)
Infrared range	20 m
Image improvements	BLC, HLC, DWDR, DAY/NIGHT MODE, 2D. DWDR. SMART IR
Day / Night	Mechanical ICR filter
Invert image (Flip)	Supports horizontal rotation of 180° and vertical rotation of 180°
Power	DC 12V / 2.04W
Video output	BNC, supports TVI, AHD, CVI and CVBS
Interface	5.5 mm
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	142mm (L) * 63mm (W) * 65mm (H)
Weight	205 g