

# CDV-70M



- **VIVID METALLIC DESIGN**

Clear and waterproof surface with AF(Anti-fingerprinting) application.

- **7 INCH WIDE LCD**

Monitor visitors via 7 inch wide display LCD.

- **VIVID DISPLAY AND AUDIO QUALITY**

It leads the world color monitor markets providing undistorted clear view and outstanding quality.

## FUNCTION

- 7 inch TFT LCD screen
- PAL/NTSC convertible
- Video talk and door lock release enable (both individual and public entrance)
- Support 2 Monitors, 2 Cameras and 2 Interphones

## SPECIFICATION

<b>Power source</b>	AC100~220V , 50/60Hz	<b>Mount type</b>	Wall-mounted type
<b>Operating temp.</b>	0°C~40°C	<b>Wiring</b>	Door camera: 4 wires Interphone: 4 wire
<b>Distance</b>	Door camera: 50m(0.65Ø) Floor Distributor: 30m(0.65Ø)	<b>Consumption</b>	Max.10W/standby 3.4W
<b>Dimension(mm)</b>	244(W)x180(H)x18(D)		

## DOOR CAMERA | DOOR CAMERA

### DRC-40K



## FUNCTION

- Illuminance sensor
- Wall-mounted type
- Built-in white LED
- Out door model
- House call and talk

## SPECIFICATION

<b>Power source</b>	12V(From monitor)	<b>Operating temp.</b>	-10°C~50°C
<b>Wiring</b>	4 wires	<b>Camera view angle</b>	Horizontal 75° / Vertical 55°
<b>Distance</b>	50m (Ø0.65)	<b>Dimension(mm)</b>	96(W)x155(H)x32(D)