

[Get a Quote](#)

Overview

Hikvision DS-8632NI-I8 is one of the Hikvision NVR 8600 Series.

Quick Spec

Table 1 shows the quick spec.

Model	DS-8632NI-I8
IP video input	32-ch
Incoming bandwidth	320Mbps
Outgoing bandwidth	256Mbps
VGA1/HDMI1 output resolution	HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA1: 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA2/HDMI2 output resolution	HDMI2: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA2: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio output	2-ch, RCA (Linear, 1 K Ω)
Decoding format	H.265/H.264/MPEG4
Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/ QCIF
Synchronous playback	16-ch
Capability	4-ch@4K/16-ch@1080p

Product Details

Hikvision DS-8632NI-I8 provides these main features:

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- Connectable to smart IP cameras from Hikvision, and the recording, play back, and backing up of VCA alarms can be realized
- Supports VCA detection alarm
- Instant playback for assigned channel under multi-channel display mode
- Smart search for the selected area in the video; and smart playback for improving the playback efficiency
- Supports HDD quota and group modes; and different capacity can be assigned to different channels

Get More Information

Do you have any question about the DS-8632NI-I8?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

DS-8632NI-I8 Specification	
IP video input	32-ch

Incoming bandwidth	320Mbps
Outgoing bandwidth	256Mbps
VGA1/HDMI1 output resolution	HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA1: 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA2/HDMI2 output resolution	HDMI2: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA2: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio output	2-ch, RCA (Linear, 1 K Ω)
Decoding format	H.265/H.264/MPEG4
Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/ QCIF
Synchronous playback	16-ch
Capability	4-ch@4K/16-ch@1080p
SATA	8 SATA interfaces
eSATA	1 eSATA interface
Capacity	500GB/1TB/2TB/3TB/4TB/5TB/6TB
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Network interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
Serial interface	RS-232; RS-485; Keyboard
USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
Alarm in/out	16/4
Power supply	100 to 240 VAC, 50 to 60 Hz
Consumption (without hard disk)	≤ 35 W
Max. Power	200 W
Working temperature	-10 to +55°C (14 to 131°F)
Working humidity	10% to 90%
Chassis	19-inch rack-mounted 2U chassis
Dimensions (W × D × H)	445 × 470 × 90 mm (17.5"× 18.3" × 3.5")

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold

18,000+

Customers Trusted

\$20,000,000

Inventory Available

50%-98%

Off Global List Price

100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com