

IP CCTV / Professional IP cameras / Uniview - Uniarch / Turret cameras

UV-IPC-T132-AF28-DL-ECO

Uniarch



Features

- Turret IP Camera
- 1/3.0" CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0.01 Lux
- IR Range 30 m
- White light range 15 m
- Compression Ultra265/H.265/H.264
- RJ45 10 M/100 M Base-TX Ethernet
- PoE IEEE 802.3af
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Range	Uniarch
Image sensor	1/3.0" CMOS
Day / Night	Mechanical ICR filter
Maximum resolution	2 Megapixel (1920x1080)
Lens	2.8 mm
FOV	Horizontal: 85.1° Vertical: 46.6° Diagonal: 95.5°
Range performance	Detect: 51.4 m Observe: 20.6 m Recognize: 10.3 m Identify: 5.1 m
Main Stream rate	1080P (1920*1080)@30fps 720P (1280*720)@30fps
Extra Stream rate	640*360@30fps 2CIF(704*288)@30fps CIF(352*288)@30fps
Compression	Ultra265/H.265/H.264
WDR	DWDR
Minimum illumination	0.005 Lux (Colour) 0 Lux with supplementary illumination
Supplementary light range	IR: 30 m White light: 15 m
Image improvements	DWDR, AGC, 2D/3D-DNR, ROI, Privacy Mask, Smart IR
Internal memory	Does not have
Alarms	Does not have
Audio	Built-in microphone
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	PoE IEEE802.3af 3.5 W max.
Interoperability	ONVIF, API, SDK
Temp. operation	-30° C ~ 60° C
Dimensions	? 118 mm

Weight 190 g

Material Plastic
