

UV-IPC3535LB-ADZK-H

Uniview



Features

- Uniview
- IP Dome Camera
- EasyBasic range
- 1/2.7" Progressive Scan CMOS
- 5 Megapixel (2880x1620)
- 2.8-12 mm motorised varifocal autofocus lens
- 0 Lux
- IR Range 40 m
- WDR 120dB
- UMD (Ultra motion detection)
- Supports corridor mode 9:16
- Compression Ultra265/H.265/H.264
- Integrated microphone
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- MicroSD slot
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Weatherproof IP67
- Vandal proof IK10

- 
- Surge protection

Specifications

Brand	Uniview
Range	Easy
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	5 Megapixel (2880x1620)
Lens	2.8 ~ 12 mm, AF autofocus and power zoom lens
Main Stream rate	5 MP(2880x1620)@25fps; 4MP (2560*1440)@25fps; 3MP (2304*1296)@25fps; 1080P (1920*1080)@30fps;
Extra Stream rate	720P (1280*720)@30fps; D1 (720*576)@30fps; 640*360@30fps
Compression	Ultra265/H.265/H.264
Minimum illumination	Colour: 0.003 lux (F1.6, AGC ON) 0 lux with IR on
Infrared range	40 m
WDR	120 dB
Image improvements	BLC, HLC, AGC, 2D/3D-NR, Smart IR, Region of interest, Privacy mask
Audio	Built-in microphone
Detection functions	Line crossing, intrusion (based on human body detection), motion detection, ultra-motion detection (UMD), tampering alarm, audio detection
Day / Night	Mechanical ICR filter
Internal memory	Micro SD slot (up to 256 GB)
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF (S-Profile, G-Profile, T-Profile)
Protection	Waterproof (IP67), Vandal-proof (IK10), Surge protection
Power	8.W, PoE (IEEE 802.3af) PoE (IEEE [%VAR%])
Operating Temp	-30°C ~ 60°C
Dimensions	?128mmx100mm