

RACKS

PDU RACKMOUNT
POWER STRIP[Product Web Page](#)

NS-506PDU08

THIS POWER DISTRIBUTION SYSTEM CONSOLIDATES YOUR POWER SOURCE AND ENABLES YOU TO CONTROL ALL POWERED DEVICES FROM ONE SWITCH.



PDU RACKMOUNT POWER STRIP 8 WAYS

FEATURES

- way single-phase PDU for electrical equipment, ideal for networking, telecom, security and audio/video.
- Built-in 2 m power cord with EU CEE 7/7 (Type E/F) plug.
- Illuminated two-pole on/off safety switch with protective cover to prevent accidental shutdown.
- Sockets with increased touch protection through contact shutters.
- Horizontal 1U 19" rack-mount installation.
- Angled outlet orientation.
- Durable aluminum construction.
- Grounding point to protect equipment from external electrical surges.
- Bracket installation style: frontal.
- For indoor use only.
- Customization requests welcome.

PACKAGE CONTENTS

19" 1U Rack Mount 9-Output Power
Distribution Unit (PDU)

ELECTRICAL

- AC input: 220.0 - 250.0 V; 50 - 60 Hz.
- Operating voltage: 230.0 V.
- Plug standard: EU CEE 7/7 (Type E/F); IEC 60884.
- Socket/outlet standard: EU CEE 7/3 (Type F); IEC 60884.
- Maximum load: 4,000.0 W.
- Overload protection: 16.0 A maximum load current.

PHYSICAL


- Dimensions (L x W x H): 45 x 484 x 45 mm.
- 1U rack mount.
- Cable length: 2 m.
- Cable type: H05VV-F 3G 1.5 mm².
- Socket angle: 35°.
- Net weight: 750 g.
- Gross weight: 850 g.
- Housing: aluminum.

TECHNICAL SPECIFICATION

Model	Way	U	Width	Height	Depth	Weight
NS-506PDU06	6	1	483	45	45	850
NS-506PDU08	8					900
NS-504PDU09	9					950



FRONT VIEW



REAR VIEW

