

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-104S3-P4-ECO

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 4 CH
- 4 CH PoE
- 64 Mbps bandwidth supported
- Maximum resolution 6 Megapixel
- Supports intelligent functions
- Ultra compression 265/H.265/H.264
- Audio output
- Simultaneous HDMI Full HD and VGA output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 6 TB
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible

Specifications

Brand	Uniarch
Inputs for IP cameras	4 IP channels / 4 PoE channels
IP compatible cameras	UNIVIEW, ONVIF (Profile S, G, T)
Main Stream recording	6Mpx / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	2x6Mpx@ 30fps / 4x5MPx @ 30fps / 4x4MPx @ 30fps / 4x3MPx @ 30fps / 4x1080p @ 30fps
Bidirectional audio	1 output 3.5 mm
Video outputs	1 HDMI Full HD, 1 VGA simultaneous
Video compression format	Ultra H.265 / H.265 / H.264
Display resolution	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	64 Mbps downstream / 48 Mbps upstream
Intelligent functions from the camera	SIP: Intrusion detection, line crossing, area entry and area exit UMD (ultra motion detection) * You need an IP camera with these functions to be able to make configurations and searches from the recorder
VCA Search	Support
SIP (Smart Intrusion Prevention) from the camera	Supported in 4CH. Alarm reception only, no alarm image reception) * IP camera with SIP function required
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Smartphone App & PC Software
Power supply	DC 48 V, <6W (No hard disk)
PoE port power supply	30 W for a single port and 50 W in total
Operating temperature	-10°C ~ +55°C
Dimensions	42 mm (H) x 190 mm (W) x 195 mm (D)
Weight	1.0 Kg