

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-108E2-P8

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 8 CH
- 50 Mbps bandwidth supported
- Maximum resolution 8 Megapixel
- Compression Ultra265/H.265/H.264
- Audio output
- VGA and HDMI 4K output
- 2 x USB 2.0
- Poe IEEE 802.3af/IEEE 802.3at
- Corridor mode
- Space for 1 HDD up to 6 TB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniarch
Inputs for IP cameras	LAN port up to 8 channels
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
PoE	IEEE 802.3at, IEEE 802.3af IEEE [%VAR%]
Total bandwidth	50 Mbps downstream / 40 Mbps upstream
Main Stream recording	4K / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	1x4K @ 30fps / 1x5MPx @ 30fps / 2x4MPx @ 30fps / 4x3MPx @ 25fps / 4x1080p @ 30fps
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Smartphone App & PC Software
Power	DC 52 V / 9W
Dimensions / Weight	46(AI) x 260(An) x 243 (D) mm / 1.2 Kg