

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-108S3-P8-ECO

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 8 CH
- 64 Mbps bandwidth supported
- Maximum resolution 6 Megapixel
- Compression Ultra265/H.265/H.264
- Audio output
- Simultaneous VGA and HDMI output
- 2 x USB 2.0
- Poe IEEE 802.3af/IEEE 802.3at
- Mouse
- Space for 1 HDD up to 6 TB
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible

Specifications

Brand	Uniarch
Inputs for IP cameras	8 CH / 8 CH PoE
IP compatible cameras	UNIVIEW, ONVIF
Main Stream recording	6Mpx / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	2 x 6MP@30, 4 x 5MP@30, 4 x 4MP@30, 4 x 3MP@30, 6 x 1080p@30, 8 x 720p@30
Video outputs	1 HDMI, 1 VGA Simultaneous
Video compression format	Ultra265 / H.265 / H.264
Display resolution	1920 x 1080/60 Hz, 1920 x 1080/50 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz
General functions	Motion detection, human body detection, video loss, alarm input * To receive alarm input events, a camera with alarm inputs is required
Intelligent functions from the camera	Area intrusion, line crossing, area entrance, area exit * You need an IP camera with these functions to be able to make configurations and searches from the recorder
SIP (Smart Intrusion Prevention) from the camera	Supported in 4CH. Alarm reception only, no alarm image reception) * IP camera with SIP function required
Total bandwidth	64 Mbps downstream / 48 Mbps upstream
Bidirectional audio	1 RCA output
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
PoE	IEEE 802.3at, IEEE 802.3af
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Smartphone App & PC Software
Power supply	DC 52V / 9W
Dimensions	46 mm (H) x 195 mm (W) x 190 mm (D)
Weight	1.0 Kg