

Analogue CCTV / HD 4n1 / XVRs / Uniview / Uniarch

UV-XVR-104G3

Uniarch



Features

- Uniarch
- DVR 5n1
- 4 BNC video CH (IP-replaceable)
- AHD, TVI, CVI, CVBS, CVBS
- 24 Mbps bandwidth supported
- Maximum IP resolution 4 Mpx
- Maximum analog resolution 5 Mpx
- Audio
- HDMI and VGA output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 8 TB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniarch
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4CH BNC
Hybrid configuration	Up to 6 IP Channels (4Mpx) replacing all the BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Display resolution	1920x1080@60Hz, 1920x1080@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz
Maximum IP recording resolution	4 Mpx
Analog cameras supported	TVI / AHD: 5MP@20fps, 4MP@30fps, 1080P@30fps, 720P@60fps CVI: 5MP@20fps, 4MP@30fps, 1080P@30fps, 720P@30fps
Main Stream recording encoding	5MPLite@12fps; 4MPLite@15fps; 1080P@15FPS; 720P@25FPS
Extra Stream recording encoding	D1@12FPS; D1@15FPS; D1@25FPS
Recording method	Manual, programmed, motion detection
Internal memory	1 HDD SATA 3.5" of up to 8TB (not included)
External interface	2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet)
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12V / 8W
Dimensions / Weight	260mm x 218mm x 47mm / 1.1 kg