

Analogue CCTV / HD 4n1 / XVRs / Uniview / Uniarch

UV-XVR-108F

Uniarch



Features

- Uniarch
- DVR 5n1
- 8 BNC video CH (IP-replaceable)
- AHD, TVI, CVI, CVBS, CVBS
- 24 Mbps bandwidth supported
- Maximum IP resolution 6 MP
- Maximum analog resolution 2 MP
- Audio
- HDMI and VGA output
- 2 x USB 2.0
- Mouse
- Space for 1 HDD up to 6 TB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniarch
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	8CH BNC
Hybrid configuration	8 CH Analog + 2 CH IP Up to 10 IP channels (6 MP) replacing all BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Display resolution	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Maximum IP recording resolution	6 MP
Analog cameras supported	TVI \AHD \CVI :1080P@30FPS;720P@30FPS Supports CVBS
Main Stream recording encoding	TVI/CVI/AHD: 1080P Lite@15fps, 720P@30fps
Extra Stream recording encoding	D1@12FPS; D1@15FPS
Recording method	Manual, programmed, motion detection
UMD	Support in 8CH analogs
VCA Search	Support
Internal memory	1 HDD SATA 3.5" of up to 6TB (not included)
External interface	2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet) / RS485
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power	DC 12 V /10 W
Dimensions / Weight	42 (H) x 190 (W) x 202 (D) mm / 0.6 kg